

What is claimed is:

Sub
A1

1. An guiding device, comprising:
an elongated finger-resting surface;
an elongated upstanding section projecting upwardly from said finger-resting surface;
an elongated scale-supporting section coupled to and extending along said upstanding section with said upstanding section being positioned between said first scale-supporting section and said finger-resting surface, said scale-supporting section being inclined with respect to a guiding device supporting surface; and

an elongated first scale made of metal and having a lower surface and an upper surface, said lower surface being rigidly and unreleasably attached to said first scale-supporting section and said upper surface having first indicia to indicate predetermined lengths along said first scale, and

said finger-resting surface permitting fingers of a user gripping said guiding device to be positioned on said finger-resting surface while being protected from an implement by said upstanding section during movement of the implement along said guiding device adjacent said first scale.

Sub
B1
C1

2. A guiding device according to claim 1, wherein
said finger-resting surface is substantially flat.

3. A guiding device according to claim 1, wherein
said finger-resting surface, said upstanding section, and said scale supporting section are integrally formed as a unitary, one-piece element.

4. A guiding device according to claim 3, wherein
said finger-resting surface, said upstanding section, and said scale supporting section are formed of plastic.

5. A guiding device according to claim 1, wherein
said first scale has a non-metallic coating on said upper surface.

6. A guiding device according to claim 1, further comprising:
a substantially flat contact surface positioned beneath said finger-resting surface, said
upstanding section, and said scale supporting section to permit smooth application of said
guiding device on the working surface.

7. A guiding device according to claim 6, wherein
said contact surface includes second indicia indicating predetermined lengths along said
contact surface.

8. A guiding device according to claim 7, wherein
said second indicia is printing on said contact surface.

9. A guiding device according to claim 6, wherein
said contact surface includes an elongated recess.

10. A guiding device according to claim 1, wherein
said upstanding section is a wall having a first side facing said first scale and a second
side facing said finger-resting surface, with said first side being inclined with respect to said
scale-supporting section.

11. A guiding device according to claim 10, wherein
said second side includes a plurality of ribs.

12. A guiding device according to claim 1, wherein
said guiding device has a generally T-shaped cross-section.

13. A guiding device, comprising:
an elongated, first portion having a finger-resting surface and a bottom surface opposite
to said finger-resting surface;

an elongated, second portion extending along said first portion, said second portion
having an upstanding section and an inclined scale-supporting section, said upstanding section
projecting upwardly from said finger-resting surface and having an uppermost free end, said
upstanding section being positioned between said scale-supporting section and said first
portions, said first and second portions having a generally T-shaped cross-section; and

an elongated first scale having a lower surface rigidly and unreleasably attached to said
scale-supporting section, an upper surface having first indicia to indicate predetermined lengths
along said first scale, an innermost edge positioned closest to said free end of said upstanding
section, and an outermost edge remote from said innermost edge,

said bottom surface of said first portion being configured to be placed against a
substantially flat working surface, and said upper surface of said first scale being inclined with
respect to the working surface such that said innermost edge of said first scale is further from the
working surface than said outermost edge of said first scale, and

said finger-resting surface permitting fingers of a user gripping said guiding device to be
positioned on said finger-resting surface while being protected from an implement by said
upstanding section during movement of the implement along said guiding device, adjacent said
first scale.

14. A guiding device according to claim 13, wherein

each of said finger-resting surface and said first bottom surface of said first portion is
substantially flat, and said finger-resting surface is substantially parallel to said first bottom
surface.

15. A guiding device according to claim 13, wherein
said first portion and said second portion are integrally formed as a unitary, one-piece
element.

16. A guiding device according to claim 13, wherein
said first portion and said second portion are formed of plastic.

17. A guiding device according to claim 13, wherein
said first scale is metal.

18. A guiding device according to claim 13, wherein
said bottom surface includes second indicia indicating predetermined lengths along said
contact surface.

19. A guiding device according to claim 13, wherein
said upstanding section is a wall having a first side facing said first scale and a second
side facing said finger-resting surface, with said first side being inclined with respect to said
scale-supporting section.

20. A guiding device according to claim 13, wherein
said upstanding section includes means for gripping said upstanding section by fingers of
a user of said guiding device.

ADD
A3